

I: Interstellar Travel

Source file name: `interstellar.c`, `interstellar.cpp`, or `interstellar.java`

The *Agency for Cross-Constellation and Interstellar Space Travel* (ACIS) is ready to offer its clients space travel among several planets across the universe.

ACIS offers a list of flight options consisting of an origin planet, a destination planet, a cost, and a duration. One of the “killer” features ACIS will offer to its clients is that of being able to plan a trip between two planets under the constraint of a maximum number of stops. That is, given a natural number n , ACIS would like to offer each client the cheapest possible trip from an origin planet to a destination planet with at most n stops. Since interstellar in-flight sleep is not pleasant, it is also important to minimize the amount of time spent in a trip.

Can you help ACIS in finding an efficient algorithm for such a task?

Input

The input consists of several test cases. Each test case begins with a line with three blank-separated integers p , f , and q ($1 \leq p \leq 300$, $0 \leq f \leq 5000$, and $0 \leq q \leq 1000$), indicating the number of planets, flights, and queries, respectively. The next p lines each contains a planet name s ($1 \leq |s| \leq 30$). The next f lines each contains two planet names and two integers s_o , s_d , c , and t (separated by a blank), denoting that there is a direct flight from s_o to s_d costing c dollars ($0 \leq c \leq 10^5$) with a duration of t units of time ($0 \leq t \leq 10^5$). The next line contains a planet name s_i indicating the initial planet for the trip. The next q lines each contains a query with a destination planet name s_f for the trip and a natural number n , both separated by a blank ($0 \leq n \leq 300$). You can assume that planet names consist only of alphabetic characters, and that s_o , s_d , s_i , and s_f are in the list of p planet names.

The input must be read from standard input.

Output

For each query s_i , s_f , n output two blank-separated integers indicating the minimum cost and the corresponding minimum travel time for this cost of an interstellar trip from s_i to s_f with at most n stops. If this is not possible, then print two blank-separated asterisks (*').

Print a line with a single period ('.') between consecutive test cases.

The output must be written to standard output.

Sample Input	Sample Output
2 3 1	2 3
Earth	.
Mars	0 0
Earth Mars 2 3	10 78
Earth Mars 4 1	10 78
Earth Earth 3 2	* *
Earth	11 79
Mars 0	.
3 3 5	10 10
Tatooine	10 10
Endor	10 10
Geonosis	* *
Tatooine Endor 300 15	20 15
Endor Geonosis 10 78	25 50
Geonosis Tatooine 1 1	25 40
Endor	* *
Endor 0	
Geonosis 0	
Geonosis 4	
Tatooine 0	
Tatooine 1	
5 5 8	
Earth	
Kaishin	
Namek	
Vegeta	
NewNamek	
Earth Kaishin 10 10	
Kaishin Namek 10 5	
Kaishin Vegeta 15 30	
Earth Vegeta 25 50	
NewNamek Earth 100 1	
Earth	
Kaishin 0	
Kaishin 1	
Kaishin 2	
Namek 0	
Namek 1	
Vegeta 0	
Vegeta 1	
NewNamek 5	